



### Standard Features:

- Proven Valve Mechanics and Electronics for years of trouble-free operations with proper maintenance
- Made in USA, NSF Listed, and FDA Grade Cation Exchange Resin
- Complete Brine Tank Assembly including Brine Well, Salt Grid, Safety Brine Valve Assembly with Float, and Air Check
- 5-Year Warranty on the Media Tank and Brine Tank only
- 2-Year Warranty on the Control Valve and Resin

### Options List:

- Variety of Media options including Catalytic Carbon or other media options
- Variety of Pre-Treatment Techniques for troubled water with a variety of media options
- Stainless Steel Jackets, SS Sleeves, Neoprene Sleeves and Plastic Tank Covers/Shrouds
- Lockout Switch for Pre-Treatment
- Customization and Private Labeling

### DuraSoft Water Softener System

	DURASOFT-0750	DURASOFT-1000	DURASOFT-1500	DURASOFT-2000
Unit Size	Small	Medium	Large	Extra Large
Media Tank Size	8" x 44"	9" x 48"	10" x 54"	12" x 52"
Resin Volume	0.75 CUFT	1.0 CUFT	1.5 CUFT	2.0 CUFT
Total Exchange Capacity	24,000 Grains	32,000 Grains	48,000 Grains	64,000 Grains
Gravel Under bedding	7.5 Lbs.	10 Lbs.	15 Lbs.	20 Lbs.
Valve Type	DS-3000 Metered Valve with 3-Button PC Controller			
Electrical	Transformer 24VAC 0.4A, US Plug			
Valve Flow Rate*	19.4 GPM Service Flow Rate at 15 psi drop			
System Flow Rate*	17.0 GPM Service Flow Rate at 15 psi drop			
Max Backwash*	7.0 GPM Backwash Flow Rate at 25 psi drop			
Brine Tank Size	15" Square X 35" Height			
Bypass Size	¾"		1"	
System Dimensions	9" X 56"	10" X 60"	11" X 66"	13" X 64"
Shipping Weight System	84 Lbs.	97 Lbs.	124 Lbs.	151 Lbs.
Shipping Weight BT	17 Lbs.			

\* Actual results may vary

DISTRIBUTED BY



Assembled  
in the USA