

MINICOMM™

Mini Commercial RO System

Features

- High Rejection TFC Membranes
- High Flow Booster Pump w/transformer
- Automatic Shut-off function when tank is full
- Powder Coated, Heavy Duty Steel Frame
- Built-in Pressure Gauge 0-160 PSI, Glycerin Filled
- 10" Pre Filters inside 10" Housings
- Made with High Quality Components
- 2-Year Limited Warranty
- Automatic High Pressure and Low Pressure Switches



Commercial Kitchens

Restaurants & Bars

Pharmaceutical Applications

Laboratories



MINICOMM™

Mini Commercial RO System

Options:

- In-Line UV Lamp Stainless Steel 2.0 GPM
- Designer Faucets or Color Faucets
- Manual or Automatic Flushing Device
- 11, 20, 34, or 86 gallon storage tank
- TDS Monitor
- Delivery pump



	MINICOMM-200	MINICOMM-300
Pure Water Production GPD*	200	300
Pure Water Production GPH*	8.4	12.6
Number of Membranes	2	3
Feed Line	3/8"	3/8"
Product Line	3/8"	3/8"
Drain Line	1/4"	1/4"
Typical TDS Rejection*	96%	96%
Voltage	110V/60HZ	110V/60HZ
System Dims	15" X 9" X 18"	15" X 9" X 18"
Shipping Weight	44LB	48LB
Shipping Dims.	17" X 12" X 21"	17" X 12" X 21"

*Actual results may vary.

DISTRIBUTED BY



Assembled
in the USA