



Bluetooth Enabled Valve



Standard Features:

- Made in USA, NSF Listed, and FDA Grade Signature CS3 Metered Valve.
- Bluetooth enabled connectivity.
- 4 Cycles fully adjustable remotely
- Made in USA, NSF Listed, and FDA Grade Black Cation Exchange Resin.
- Complete Brine Tank Assembly including Brine Well, Safety Brine Valve Assembly with Float, and Air Check.
- 10-Year Warranty on the Media Tank and Brine Tank only.
- 7-Year Warranty on the Control Valve.
- 2-Year Warranty on the Softening Resin.

Options List:

- Variety of Media options including Catalytic Carbon or other media options
- Variety of Pre-Treatment Techniques for troubled water with a variety of media options
- Stainless Steel Jackets, SS Sleeves, and Neoprene Tank Covers/Shrouds
- Lockout Switch for Pre-Treatment
- Customization and Private Labeling

BlueStream Water Softener System

	BLUESTREAM-0750	BLUESTREAM-1000	BLUESTREAM-1500	BLUESTREAM-2000
Unit Size	Small	Medium	Large	Extra Large
Media Tank Size	8" x 44"	9" x 48"	10" x 54"	12" x 52"
Resin Volume	0.75 CUFT	1.0 CUFT	1.5 CUFT	2.0 CUFT
Total Exchange Capacity	24,000 Grains	32,000 Grains	48,000 Grains	64,000 Grains
Gravel Under bedding	7.5 Lbs.	10 Lbs.	15 Lbs.	20 Lbs.
Valve Type	Signature CS3 Metered Valve, Bluetooth Connected			
Electrical	Transformer 12VDC US Plug			
Valve Flow Rate*	27.0 GPM Peek Flow Rate at 25 psi drop			
System Flow Rate*	21.0 GPM Service Flow Rate at 15 psi drop			
Max Backwash*	17.0 GPM Backwash Flow Rate at 25 psi drop			
Brine Tank Size	15" Square X 35" Height			
Bypass Size	1"			
System Dimensions	9" X 56"	10" X 60"	11" X 66"	13" X 64"
Shipping Weight System	84 Lbs.	97 Lbs.	124 Lbs.	151 Lbs.
Shipping Weight BT	17 Lbs.			

* Actual results may vary

DISTRIBUTED BY



MEMBER
Water Quality
ASSOCIATION



Assembled
in the USA